(19) World Intellectual Property Organization International Bureau





(43) International Publication Date 30 October 2003 (30.10.2003)

PCT

(10) International Publication Number WO 03/089835 A1

AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC,

LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE,

SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ,

Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE,

ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO,

SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM,

(84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),

(51) International Patent Classification⁷: 11/06, G03B 17/56

F16M 13/04, (81) Designated States (national): AE, AG, AL, AM, AT, AU,

(21) International Application Number: PCT/GB03/01653

(22) International Filing Date: 17 April 2003 (17.04.2003)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

0208977.9

19 April 2002 (19.04.2002) GB

(71) Applicant and

(72) Inventor: SMITH, Howard, James [GB/GB]; Unit 2B Whitehall Street, Stockport, Cheshire SK5 7LW (GB).

GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).


Published:
 with international search report


VC, VN, YU, ZA, ZM, ZW.

(74) Agent: RUSSELL-RAYNER, Albert, Patrick; Business Centre West, Avenue One, Business Park, Letchworth Garden City, Hertfordshire SG6 2HB (GB).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: ARTICLE MOUNTING





V U U3/U09/03

(57) Abstract: An arrangement for eccentrically mounting an camera a support arrangement (I) incorporating two main portions (2, 3, 7) that are adapted for relative rotation about a predetermined axis defined by the orientation of the support arrangement with respect to the horizontal/vertical in such manner that in the event of said relative rotation a predetermined axis of the article/apparatus/camera effectively remains in its initial position. An electric motor mounted on one portion (2, 3), the motor being arranged to rotate a gear/pinion (9, 32, 33) engaging with a tooth rack (8, 27, 31) coaxial with said direction and provided upon the said other portion. The arrangement is combinable with an adjustable level article support unit including telescopically engageable sections (2, 5, 12, 13) including a main post section (2) and at least two further post sections (5, 12; 5, 12, 13) that are adapted to be independently positional set with respect to the main section.